

**Features:**

- UL 1449 Fourth Edition Listed
- 150kA – 200kA per phase ratings
- All UL required OCP & Safety Coordination included inside
 - Type 2 SPDs intended for Load Side of Main Disconnect
- 20kA Inominal (I_n)
- 200kA SCCRs (most models)
- UL 96A Lightning Protection Master Label compliant
- Voltage Specific Design – Highly configurable
- All MOV suppression elements monitored
- All Modes of Protection

Performance Specifications**Surge Capacities (L-N, L-G, N-G, L-L)****150kA Per Phase****200kA Per Phase**

- UL 1449 Fourth Edition Listed Type 1, CSA 22.2 No. 269.1
- Optional UL 1449-4 Type 2 SPD, UL 1283 Listed, CSA 22.2 No. 269.2
- UL 1449-4 tested Inominal (I_n): 20kA
- UL 1449-4 tested SCCR: 200kA & 100kA
- UL 1449-4 Voltage Protection Ratings (VPRs):
 - 208Y/120V: as low as 600V
 - 480Y/277V: as low as 1000V (data table on back)
- Less than 1 nanosecond response time
- Repetitive Impulse: 5,000 hits
- AC Sinewave Tracking Filter with EMI/RFI Filtering up to -50dB from 10kHz to 100MHz (Type 2 option only, incl. UL 1283 Listing)

Physical Specifications

- Relative Humidity Range: 0 - 95% non-condensing
- Operating Frequency: 47 - 63Hz
- Peak Operating Temperature: +85°C (185°F)
- Operating Temperature: -25°C (-15°F) to +60°C (140°F)
- Weight: 5 lbs (2.3 kg)
- NEMA 4X Polycarbonate enclosure – UL 746C(f1) & UL 94-5VA
- Dimensions: 6" x 6" x 4" (152mm x 152mm x 102mm) (excluding removable mounting feet)
- Lug size: #8 - #14 AWG
- Typical connection: #8 AWG and 40A breaker

Design Features

- Designed, Manufactured & Tested consistent with:
 - ANSI/IEEE C62.41.1-2002, C62.41.2-2002, C62.45-2002, C62.62-2010, C62.72-2016, IEEE SA 1100-2005 (Emerald Book)
 - NEC® Article 285
 - NEC® Articles 620.51(E), 645.18, 670.6, 695.15, 700.8 and 708 requiring SPDs
 - Complies with UL 96A 12th Edition master label requirements for lightning protection systems and NFPA 780 Lightning Protection
 - IEC 61643, CE
- High Energy Parallel Design for Category C3 & C-High applications
- For External Mounting next to Switchgear, Motor Controls Centers or Panelboards
- Individually Fused & Thermally Protected MOVs
- Large-Block, 34mm square, 50kA MOVs
- Solid State Bidirectional Operation

Diagnostic Monitoring

- 100% monitoring – Every MOV is monitored, incl. N-G
- Green LED Status indicator per phase
- Red LED service indicator
- Phase Loss monitoring (toggles LED & dry contact)
- Electrically isolated circuitry ensures surges do not damage diagnostics
- Audible Alarm & Form C Dry Contact (Contact rated 24V, 2A)

Quality, Standards & Validation

- Type 2 (Opt.): UL 1449 Fourth Edition, CSA No. 269.2, UL 1283
- UL file: VZCA.E321351 at www.UL.com
- RoHS-compliant
- IEC 61643, CE
- 10 year warranty (longer optional)
- Burn-In tested prior to shipment
- ISO 9001:2008 Quality Management System
- ISO 17025:2005 Laboratory Qualification



TEXDS Model Number Configurator & Options

TE XDS 4X A 2 M

Voltage Code for Electrical System

Common North American Systems:

- 01 = 254/127V Split Phase - 1Ø 3W+Grnd (Fig 1)
- 02 = 220/127V Wye - 3Ø 4W+Grnd (Fig 2)
- 04 = 480Y/277V Wye - 3Ø 4W+Grnd (Fig 2)
- 05 = 480V Delta - 3Ø 3W+Grnd (Fig 3) & HRG Wye *

* Available in 200 kA only

Surge Current Rating

- 15 = 150kA/Phase
- 20 = 200kA/Phase


Enclosure Rating

4X = NEMA 4X
Non-Metallic
(size 6" x 6" x 4")

- 2 = Type 2 SPD, incl. UL 1283 EMI/RFI Filters
- *Standard

Monitoring

A = Audible Alarm & Dry Contacts, Form C, 240V, 5A (Standard)



Performance Data

Common Voltages		UL 1449 Fourth Edition Test Data						
		Voltage Protection Ratings (VPR - 3kA)				I _n	SCCR	MCOV
		L-N	L-G	N-G	L-L			
01	= 240/120V Split Phase	700	700	700	1200	20kA	100kA	150
02	= 208Y/120V 3Ø Wye	700	700	700	1200	20kA	200kA	150
02	= 220Y/127V 3Ø Wye	700	700	700	1200	20kA	200kA	150
04	= 480Y/277V 3Ø Wye	1200	1200	1200	2000	20kA	200kA	320
04	= 415Y/240V 3Ø Wye	1200	1200	1200	2000	20kA	200kA	320
04	= 400Y/230V 3Ø Wye	1200	1200	1200	2000	20kA	200kA	320
04	= 380Y/220V 3Ø Wye	1200	1200	1200	2000	20kA	200kA	320

Other Available Systems:

Please see supplementary data sheet, contact us at info@pqglobal.com, or confirm at www.UL.com using CCN of VZCA